

SCM200ASL PRO: 3-way active*



Features

- 34mm soft dome tweeter.
- Twin full spec "SL" 12"/314mm bass drivers.
- ATC 75mm "Super Dome" mid driver.
- Rack-mount ATC 4 way grounded plane 850W amplifier.
- Clip indication.
- 6 year warranty.

Specifications

Drivers : HF 34mm, Mid 75mm, LF 2 x 314mm

Amplitude Linearity ($\pm 2\text{dB}$) : 60Hz-12kHz

Cut-off Frequencies (-6dB) : 32Hz, 20kHz (free standing) 25Hz, 20kHz (soffit mounted)

Horizontal Dispersion : $\pm 80^\circ$, Coherent

Vertical Dispersion : $\pm 10^\circ$, Coherent

Max. Continuous SPL (1 metre) : 118dB

Crossover Frequencies : 380Hz, 3.5kHz

Input Connectors : Male XLR

Input Sensitivity : 2V

Input Impedance : Balanced $> 10\text{k}\Omega$

Amplifier Output : Bass 275+275W, Mid 200W, High 100W

Filters : Even Order Critically Damped

Overload Protection : Active FET momentary gain reduction plus thermal tweeter protection

Front Panel Indicators : Power On indicator, Gain Reduction warning

Dimensions (HxWxD) : 830 x 730 x 440mm (32.7" x 28.7" x 17.3")

Weight : 116kg / 255.2lbs

*Passive versions available.

ATC reserves the right to vary products and specifications without prior notice.



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk