

DRAWMER

1972 Dual Mic/Line/Instrument Preamp



The Drawmer 1972 is a 2-channel Dual Mic, Line, and Instrument Preamp with a flexible feature set to fit any recording session. The 2 independent mic preamps feature THAT Corporation technology to provide ultra clean and transparent recordings. Selectable variable impedance allows you to optimally match the 1972 to any microphone from budget to high-end mics, and also ribbon mics. The input features 12 stepped input gain settings and a variable output trim for fine tuning. Tone shaping features include LoCut, HiCut, and Shape. The unique Lift feature is a single switch solution to recording low signal levels. Each channel also features a VU meter with a +10db pad adjustment for hot output level metering.

Specifications:

INPUT

Input Impedance 20k Ohms or greater
Maximum Input Level +21dBu

OUTPUT

Output Impedance 100 Ohms
Maximum Output Level +21dBu into 10k Ohms Load

FREQUENCY RESPONSE

20Hz to 20kHz +/-0.5dB

CROSSTALK

< -85dB @ 1kHz

NOISE AT UNITY GAIN

20Hz - 20kHz >92dB

% DISTORTION (THD & NOISE) @ 1kHz

0dB 0.07%

10dB 0.07%

MIC EIN

-130dB Aweighted

POWER REQUIREMENTS

230Volt or 115V at 50-60Hz, 15VA

FUSE RATING

T160mA for 230Volt,
T315mA for 115Volt
Conforming to IEC 127-2

FUSE TYPE

20mm x 5mm, Class 3 Timed-Blow, 250Volt working

CASE SIZE

482mm (W) x 44mm (H) x 200mm (D)
19" x 1.75" x 8"

WEIGHT

2.6Kgs

5.9lbs